

DynaHawk™ WH Series


Full HD Multiple Streams Micro Box IP Camera (WiFi / PoE)



The Full HD Multiple Streams Micro Box IP Camera is not only an easy setup camera, but a versatile solution for homes and small offices. For WiFi model, users can install the wireless IP camera in any place with Wi-Fi access. In addition, the both type of micro box camera has built-in microphone and speaker which allows two-way audio communication. For low light environments, the IP camera has incorporated Day/Night ICR technologies to capture clear images. 2 Megapixel resolution is supported for providing high definition images. Quad Streams Compression (H.264 Baseline / Main / High Profile + MJPEG) are available for efficient bandwidth and storage management. Users now can remotely and clearly watch over their families and homes via mobile devices while they are at work or even traveling.

Key Features

- Progressive Scan CMOS Sensor
- 2M Resolution
- Quad Streams Support
- Dual streams- Full HD 1080P Real-time + D1 Real-time
- Quad Streams Compression- H.264 Baseline / Main / High Profile + MJPEG
- Multi-language Support
- Wireless Network Support (WiFi model only)
- Wide Dynamic Range
- Built-In Microphone and Speaker*
- Motion Detection
- Privacy Masks
- Smart Picture Quality / 3D Noise Reduction
- Smart IR Mode
- Day/Night (ICR)
- IR LED Module (working distance up to 5 m)*
- microSD Support
- ONVIF Support



DynaHawk™ WH Series - Micro Box IP Camera

Camera		W2V1-H	W2S1-H
Image Sensor		1/2.7" Progressive CMOS	1/2.8" Progressive CMOS
Effective Pixels			1920(H) x 1080(V)
Minimum Illumination		0.2 lux (color)/ 0.02 lux (B/W) @30 IRE	
Shutter Speed		1 ~ 1/10000 sec.	
Lens			
Lens		Board lens	
Focal Length		2.8 mm / 3.6 mm	
F Number		F 2.0 / F 1.8	
FOV		105° / 87.6°	90.34° / 71.8°
Operation		English / French / German / Italian / Japanese / Korean / Portuguese / Russian / Simplified Chinese / Spanish / Traditional Chinese	
Multiple Languages		English / French / German / Italian / Japanese / Korean / Portuguese / Russian / Simplified Chinese / Spanish / Traditional Chinese	
Backlight Compensation		On / Off	
White Balance		Manual / AWB / ATW / One Push	
3D Noise Reduction		On / Off	
Wide Dynamic Range		On / Off	
Privacy Mask		On / Off	
Brightness		Manual	
Exposure		Auto / Manual	
Sharpness		Manual	
Contrast		Manual	
Saturation		Manual	
Hue		Manual	
Digital Zoom		Support	
Motion Detection		On / Off / By Schedule	
Privacy Mask Type		Color	
ICR		Auto / On / Off / Smart	
ICR+IR LED*		Auto / LED On / LED Off / Smart IR / Light Sensor	
Tampering Alarm		On / Off / By Schedule	
Two-way Audio		Embedded Mic in / Embedded Speaker Out*	
Audio	Compression	G.711/G.726	
Network			
Interface		RJ-45, 10/100 Mbps Ethernet	
Video Compression		H.264 (MPEG-4 Part 10/AVC) / MJPEG	
Video Streaming		Dual Streams H.264 + MJPEG / H.264 + H.264 Quad Streams H.264*3 + MJPEG / H.264*4	
Video Resolution		H.264- Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF MJPEG- Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF	
Frame Rate		Dual Streams : 1080p (30/25 fps) + D1 (30/25 fps)	
Protocol		ARP, IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF	
Security		PoE: HTTPS / IP Filter / IEEE 802.1X WiFi: HTTPS / IP Filter / IEEE 802.1X (WPA, WPA2)/Shared Key/Pair-wise Key	
Alarm	Input	1 Set 5V 10kΩ pull up	
	Output	1 Set Photo Relay Output 300V DC/AC	
Event Notification		HTTP / FTP / SMTP	
Micro SD		microSDHC 32GB support	
Supported Web Browser		Internet Explorer (6.0+) / Chrome / Firefox / Safari	
User Account		20	
Password Levels		User and Administrator	
Mechanical			
Built-in IR Illuminator*	Working Distance	up to 5 m	
	Wavelength	850 nm	
	Number of LEDs	2	
LED Indicator		PoE: Power / Link / ACT ; WiFi: Power (Green) / WiFi (Orange)	
Connectors	Alarm	4 Pin Terminal Block	
	Power	PoE: DC Jack / WiFi: Micro USB (with 1A USB charger)	
	Ethernet	PoE: RJ-45 ; WiFi: N/A	
General			
Operating Temperature		-10°C ~ 50°C (14° ~ 122° F)	
Humidity		10% ~ 90%, No Condensation	
Weatherproof Standard*		IP66	
Dimension		96.51 x 56 x 61.4 mm (3.78 x 2.2 x 2.42 in.)	
Weight		120g	
Power Source		PoE: DC 12V / PoE ; WiFi: 1A USB charger	
Power Consumption		WiFi: System 3 W (Built-in IR Illuminator: +0.8W) PoE: System 3.2 W (Built-in IR Illuminator: +1W)	WiFi: System 3.2 W (Built-in IR Illuminator: +0.8W) PoE: System 3.4 W (Built-in IR Illuminator: +1W)
Regulatory		CE / FCC	

* mark for optional items

Product specification and availability are subject to change without notice.



DYNACOLOR, INC.

No. 116, Jou Tz Street, Neihu, Taipei 114, Taiwan

TEL: (886)2-2659-8898

FAX: (886)2-2659-8868

<http://www.dynacolor.com.tw>

info@dynacolor.com.tw